

## Impulse Nail Packs

### Value Packs (3000 nails and 3 Fuel Cells)

Part N°	Length x Diameter	Shank Type / Finish
B20544V	50 x 2.87mm	Smooth / Bright
B20565V	50 x 2.87mm	Smooth / Hot Dip Gal
B20573V	50 x 2.87mm	Screw / E Gal Hardened
B20546V	65 x 2.87mm	Smooth / Bright
B20567V	65 x 2.87mm	Smooth / Hot Dip Gal
B20568V	65 x 2.87mm	Ring / Hot Dip Gal
B20547V	75 x 3.06mm	Smooth / Bright
B20563V	75 x 3.06mm	Ring / Bright
B20569V	75 x 3.06mm	Smooth / Hot Dip Gal
B20548V	82 x 3.15mm	Smooth / Bright
B20570V	82 x 3.15mm	Smooth / Hot Dip Gal
B20550V	90 x 3.15mm	Smooth / Bright
B20571V	90 x 3.15mm	Smooth / Hot Dip Gal

### Handy Packs (1000 nails and 1 Fuel Cell)

Part N°	Length x Diameter	Shank Type / Finish
B20552	50 x 2.87mm	Smooth / Hot Dip Gal
B20553	65 x 2.87mm	Smooth / Hot Dip Gal
B20556	65 x 2.87mm	Ring / Hot Dip Gal
B20551	75 x 3.06mm	Smooth / Bright
B20554	75 x 3.06mm	Smooth / Hot Dip Gal
B20559	75 x 3.06mm	Ring / Hot Dip Gal
B20555	82 x 3.15mm	Smooth / Hot Dip Gal
B20550	90 x 3.15mm	Smooth / Bright
B20571	90 x 3.15mm	Smooth / Hot Dip Gal

### DekFast Value Pack (3000 nails and 3 Fuel Cells)

Part N°	Length x Diameter	Shank Type / Finish
B20561V	50 x 2.87mm	Ring / Mechanical Gal
B20562V	65 x 2.87mm	Ring / Mechanical Gal

### DekFast Handy Pack (1000 nails and 1 Fuel Cell)

Part N°	Length x Diameter	Shank Type / Finish
B20557	50 x 2.87mm	Ring / Mechanical Gal
B20558	65 x 2.87mm	Ring / Mechanical Gal

Contact | Paslode Australia

Head Office

47 - 55 Williamson Road  
Ingleburn  
NSW 2565  
Australia

[www.paslode.com.au](http://www.paslode.com.au)

Note:

Tests undertaken by the University of Technology, Sydney, have confirmed that the Paslode 75x3.06mm gun driven nail and the Duo-Fast 75x3.06mm gun driven nail comply with the performance requirements of AS1684.2 & 3 -1999 "Residential Timber-Framed Construction" Clause 9.5 and satisfy the Standard's requirements for "Nominal Fixings."

Your nearest distributor:



A Division of ITW Australia Pty Ltd  
ABN 63 004 235 063

# Paslode®

[www.paslode.com.au](http://www.paslode.com.au)



## Impulse FrameMaster Strip Nailer

## Impulse FrameMaster

**Tougher** new engine design eliminates the use of rubber O-rings providing greater reliability with less servicing.

**Faster** dramatically reduced actuation force combined with improved skew nailing helps get the job done faster and easier.

**Smarter** all new fuel delivery system ensure greater reliability with easier loading.

## Product Specification

Product code	B20540
Weight	3.1kg
Height	368mm
Length x Width	305 x 105mm
Nail range	50mm - 90mm
Collation Angle	34 Degree

## Cycle Rates

Cycle rates	2 - 3 nails / sec.
Maximum cycle	1,000 / hour
Magazine capacity	approx. 45
Fuel cell	approx. 1000
Battery	approx. 4000 fixings per charge
Charger	max. 2 hours

## Applications

- Framing
- Flooring
- Roofing
- Eaves
- Trusses
- Joists
- Decking
- Cladding

## Impulse FrameMaster



## TWIST N LOCK

The Twist'n'Lock fuel cell has in-can metering. The force needed to activate the FrameMaster has been reduced by 40% making overhead nailing much easier.



## Features & Benefits

- 1 Twist N Lock fuel system (In-Can)**  
Reduces actuation force by 40% making overhead nailing much easier
- 2 Improved engine**  
Top rubber o'ring has been replaced by long lasting steel seal rings
- 3 Easy to remove filter**  
Keeps engine running more efficiently
- 4 Rubber moulded hand grip**  
Providing increased user comfort
- 5 Belt hook / rafter hook combination**  
Keeps tool secure and also off the ground while not in use
- 6 Rearload magazine**  
For fast & easy nail loading
- 7 Tool free depth adjustment**  
Provides precise control of nail depth
- 8 Lower probe with skew nailing teeth**  
Helps to bite into the timbers to ensure positive placement of the fastener

